

Hammer smooth metalpaint smooth 250 ml, 750 ml, 2,5l and 10l

MASTON

MASTON

HAMMER



DIRECT TO RUST!



ALL ROUND METALPAINT

Rustprotection + Primer + Surface paint = Hammer metalpaint

MASTON HAMMER smooth

All round Maston Hammer Smooth metal paint, you can handle all metal surfaces, both indoors and outdoors. All in one: rust protection, primer and surface paint. Glossy, tough and hard-wearing, durable surface with only one application. You can paint new and old metal and even directly onto rust. Also, previously painted iron and steel surfaces are easy to paint with Maston HAMMER metallic paint. Suitable also on wooden surfaces. Application conditions : The temperature +10 - + 25 ° C, air relative humidity 30-80%.

Preparations:

Remove loose rust and flaky paint from the treatable surface using a steel brush. Remove any grease and dirt. Dry the moist surface before the paint application. Mix the paint carefully before use and between applications.

Painting:

- **Using a brush:** Use a wider brush. Apply the paint as a thick uniform coat applying transverse brushing movements. Finish the surface with light strokes. Repaint, if necessary, within 2-8 hours or after 8 days (+20°C) only with itself, Maston Hammer Smooth paint.
- **Using a roller:** use a paint roller of natural fibre. Cover the surface uniformly. Dilute the paint with xylene, if necessary.

CHARACTERISTICS:

Usage: For indoor and outdoor usage.
Adhesion: excellent adhesion (Zn- and Al-surfaces needs ackryl primer).
Chemical resistant: excellent
Weather resistant: excellent, dry painted surface repels water and dirt
Base: Alkydpoint
EU VOC-content: II B(e),VOC max. 840g/L (2010), VOC 354,28g/L
Coverage m2/l: 5,0 – 6,0 *)
Dilution and washing the tools: xylene.

Drying time: Touch-dry: 2 h, Dry: 24 h. Repaint, if necessary, within 2-8 hours or after 8 days (+20°C) only with itself, Maston Hammer Smooth paint.
Heat resistant: +120 °C

CONTENTS: 250 ml, 750 ml, 2,5l and 10 l

*) PLEASE NOTE! The coverage will depend upon many factors including texture, porosity, color shade and moisture content of the substrate. Drying time will depend upon material, humidity and air temperature as well as thickness of the layer/'s painted.



Maston Oy • www.maston.fi • maston@maston.fi

Teollisuustie 10, FI-02880 Veikkola, Finland, Tel. +358 20 7188 580, Fax +358 20 7188 599

Теоллисууде 10, 02880 Вейккола, Финляндия, Тел. +358 20 7188 580, Факс. +358 20 7188 599



Hammer smooth metalpaint smooth 250 ml, 750 ml, 2,5l and 10l

MASTON
250 ml


Art nr. 886001
Black



Art nr. 886002
White



Art nr. 886003
Silver



Art nr. 886004
Green



Art nr. 886006
Red



Art nr. 886007
Blue



Art nr. 886008
Brown



Art nr. 886009
Yellow

750 ml


Art nr. 8861001
Black



Art nr. 8861002
White



Art nr. 8861003
Silver



Art nr. 8861004
Green



Art nr. 8861006
Red



Art nr. 8861007
Blue



Art nr. 8861008
Brown



Art nr. 8861009
Yellow

2,5 l


Art nr. 886201
Black



Art nr. 886202
White



Art nr. 886203
Silver



Art nr. 886204
Green



Art nr. 886207
Blue



Art nr. 886206
Red



Art nr. 886208
Brown



Art nr. 886209
Yellow

10 l


Art nr. 8861101
Black



Art nr. 8861102
White



Art nr. 8861103
Silver



Art nr. 8861104
Green



Art nr. 8861107
Blue



Art nr. 8861106
Red



Art nr. 8861108
Brown



Art nr. 8861109
Yellow



Maston Oy • www.maston.fi • maston@maston.fi

Teollisuustie 10, FI-02880 Veikkola, Finland, Tel. +358 20 7188 580, Fax +358 20 7188 599

Теоллисуостие 10, 02880 Вейккола, Финляндия, Тел. +358 20 7188 580, Факс. +358 20 7188 599

